

QCK-3-26.5-3

3.5mm Connectors, DC~26.5GHz, 3-in-1

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with 3.5mm connectors from DC to 26.5 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size
		(GHz)	(Ω)	(Max.)	(°, Max.)			(mm)
Opens	3.5mm open	DC~26.5	50	-	± 1.5	Gold plated beryllium copper	Passivated stainless steel	-
Shorts	3.5mm short			-	± 1.5			-
Coaxial Terminations	3.5mm termination			1.055	-			-
Connect Joint ¹				-	-	Aluminium oxide		-
QA33C-MM-1 ²	3.5mm male 3.5mm male adapter			1.06	-	Gold plated beryllium copper	Gold plated beryllium copper	-
QA33C-FF-3 ²	3.5mm female 3.5mm female adapter							-
Storage Box				-	-	-	-	Wood

[1] The Connect Joint connects the Opens, Shorts and Coaxial Terminations

[2] Equal phase adapter

How To Order

QCK-3-26.5-3-M 3-in-1, male, including open, short and termination.

QCK-3-26.5-3-F 3-in-1, female, including open, short and termination.

To order a single component, specify the part number in the first column.