

## QCK-K-40-1

### 2.92mm Connectors, DC~40GHz, Precision type

Features:  
\* High Precision

Applications:  
\* Calibration  
\* Laboratory Test



#### Description

With the components in these kits you can make error-corrected measurements of devices supplied with 2.92mm connectors from DC to 40 GHz.

#### Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size		
		(GHz)	( $\Omega$ )	(Max.)	( $^{\circ}$ , Max.)			(mm)		
QOKC-M-40-1	2.92mm male open	DC~40	50	-	$\pm 6$	Gold plated beryllium copper	Gold plated beryllium copper	-		
QOKC-F-40-1	2.92mm female open									
QSKC-M-40-1	2.92mm male short			-	$\pm 4.5$			-		
QSKC-F-40-1	2.92mm female short									
QCT-K-C-M-40-1	2.92mm male termination			1.08	-			-		
QCT-K-C-F-40-1	2.92mm female termination									
QW-K1-CK	2.92mm torque wrench			-	-			Nickel plated tool steel (Head)	Aluminium, anodised (Handle)	8.1 (Opening size)
QAKKC-MM*	2.92mm male to 2.92mm male adapter			1.15	-			Gold plated beryllium copper	Gold plated beryllium copper	-
QAKKC-MF*	2.92mm male to 2.92mm female									
QAKKC-FF*	2.92mm female to 2.92mm female									
Storage Box		-	-	-	-	Wood	275*200*80/ 145*145*60			

“\*” Equal phase adapter

#### How To Order

- QCK-K-40-1-10** All the 10 components in one box.
- QCK-K-40-1-3M** Three in one box, including open, short and termination, male, QOKC-M-40-1, QSKC-M-40-1, QCT-K-C-M-40-1.
- QCK-K-40-1-3F** Three in one box, including open, short and termination, female, QOKC-F-40-1, QSKC-F-40-1, QSKC-F-40-1.
- QCK-K-40-1-6** Six in one box, including QCK-K-40-1-3M and QCK-K-40-1-3F.

To order a single component, specify the part number in the first column.