

QCK-N-18-1

N Connectors, DC~18GHz, Precision type

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with N connectors from DC to 18 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size			
		(GHz)	(Ω)	(Max.)	($^{\circ}$, Max.)			(mm)			
QONC-M-18-1	N male open	DC~18	50	-	± 1	Gold plated beryllium copper	Passivated stainless steel	-			
QONC-F-18-1	N female open			-				-			
QSNM-M-18-1	N male short			± 1	-			-			
QSNM-F-18-1	N female short				-			-			
QCT-N-C-M-18-1	N male termination			-	1.048			-	-		
QCT-N-C-F-18-1	N female termination			-				-			
QW-N1-CK	N torque wrench			-	-			-	Tool steel (Head)	Aluminium, anodised (Handle)	19.1 (Opening size)
QANNC-MM-1*	N male to N male adapter			1.06	-			-	Gold plated beryllium copper	Passivated stainless steel	-
QANNC-MF-1*	N male to N female adapter										-
QANNC-FF-1*	N female to N female adapter										-
Storage Box		-	-	-	-	Wood	275*200*80/ 145*145*60				

“*” Equal phase adapter

How To Order

QCK-N-18-1-10 All the 10 components in one box.

QCK-N-18-1-3M Three in one box, including open, short and termination, male, QOKC-M-18-1, QSKC-M-18-1, QCT-K-C-M-18-1.

QCK-N-18-1-3F Three in one box, including open, short and termination, female, QOKC-F-18-1, QSKC-F-18-1, QCT-K-C-F-18-1.

QCK-N-18-1-6 Six in one box, including QCK-N-18-1-3M and QCK-N-18-1-3F.

To order a single component, specify the part number in the first column.