

# Coaxial Power Dividers

## General Specifications

- Frequency: 12MHZ-18GHZ
- Working temperature: -55°C~+85°C



## Product Reference

Frequency (GHz)	Ways	Insertion Loss (dB)	Isolation (dB)	VSWR	Phase Balance (°)	Power Handling (CW)	Impedance (Ω)	Connector	Size (mm)
0.5~2	2	≤0.50	≥20	≤1.25	≤±2	≤10	50	SMA	60×30×10
1~8	2	≤1.50	≥18	≤1.50	≤±5	≤10	50	SMA	30×50×10
2~18	2	≤1.20	≥18	≤1.50	≤±5	≤10	50	SMA	24×47×10
1~2	4	≤0.60	≥20	≤1.25	≤±3	≤10	50	SMA	56×54×10
4~8	4	≤1.00	≥20	≤1.35	≤±3	≤10	50	SMA	56×54×10
6~18	4	≤1.50	≥18	≤1.60	≤±8	≤10	50	SMA	56×45×10
0.5~2	8	≤1.50	≥20	≤1.40	≤±5	≤10	50	SMA	108×108×10
2~4	8	≤0.90	≥20	≤1.30	≤±5	≤10	50	SMA	108×64×10
4~8	8	≤1.40	≥20	≤1.50	≤±5	≤10	50	SMA	108×64×10
6~18	8	≤2.50	≥18	≤1.80	≤±8	≤10	50	SMA	108×45×10
2~8	16	≤2.60	≥18	≤1.60	≤±5	≤20	50	SMA-Female	