

同轴环形器(coaxial circulator)

【特点】 (high light)

1. 低损耗, 高隔离度, 高功率容量 (low IL, high isolation, high power)

2. 可定制频率范围: 0.3-18GHz (FREQ: 0.3~18 GHz)



频率范围 (freq.) (GHz)	带宽 (BW) (MHz)	插损(IL) (dB)max	隔离(ISO) (dB)min	驻波 (VSWR)	功率容量 (power) (CW)	接头 (connector)
0.3-0.6	50	0.3	23	1.20	100W	SMA/N
	100	0.4	20	1.25	100W	SMA/N
0.6-0.86	full	0.5	15.5	1.40	100W	SMA
0.8-2.3	100	0.3	20	1.20	100W	SMA
	200	0.4	19	1.25	100W	SMA
1-1.2	full	0.4	20	1.20	100W	SMA
1.2-1.4	full	0.3	20	1.20	100W	SMA
1.6-1.8	full	0.4	19	1.25	100W	SMA
1.8-2	full	0.3	20	1.20	100W	SMA
2-2.4	full	0.5	19	1.25	100W	SMA
2-4	300	0.3	20	1.20	100W	SMA
2.15-2.8	full	0.5	16.5	1.35	100W	SMA
2.3-2.5	full	0.3	20	1.20	100W	SMA
2.5-3.4	full	0.5	16.5	1.35	100W	SMA
2.7-3.1	full	0.4	20	1.20	100W	SMA
3.1-3.4	full	0.3	20	1.20	100W	SMA
4.4-5	full	0.25	23	1.15	10W	SMA
4-8	1000	0.3	20	1.20	10W	SMA
5-6	full	0.25	20	1.20	10W	SMA
8.5-9.6	full	0.3	20	1.20	10W	SMA
9-10	full	0.3	20	1.20	10W	SMA
10-11	full	0.3	20	1.20	10W	SMA
6-12	1000	0.3	20	1.20	10W	SMA
8-18	500	0.3	25	1.15	5W	SMA
	1000	0.3	23	1.20	5W	SMA
	2000	0.4	20	1.2	5W	SMA