



同轴隔离器(coaxial isolator)

【特点】 (high light)

1. 低损耗, 高隔离度, 高功率容量 (low IL, high isolation, high power)
2. 可定制频率范围: 0.3-18GHz (FREQ: 0.3~18 GHz)

频率范围 (FREQ) (GHz)	带宽(BW) (MHz)	插损(IL) (dB)max	隔离(ISO) (dB)min	驻波 (VSWR) max	通过功率 (FWD) (CW)	负载 功率 (REV) (CW)	接头 (connector)
0.3-0.6	50	0.3	23	1.20	100/400W	1/10/60/100W	SMA/N
	100	0.4	20	1.25	100/400W	1/10/60/100W	SMA/N
0.6-1.8	100	0.3	23	1.20	100/400W	1/10/60/100W	SMA/N
	200	0.4	20	1.25	100/400W	1/10/60/100W	SMA/N
0.6-0.86	full	0.5	16	1.40	100/400W	1/10/60/100W	SMA/N
1-1.2	full	0.4	20	1.20	10/100W	1/10/60/100W	SMA
1.2-1.4	full	0.3	20	1.20	10/100W	1/10/60/100W	SMA
0.8-2.3	100	0.3	20	1.20	10/100W	1/10/60/100W	SMA
	200	0.4	19	1.25	10/100W	1/10/60/100W	SMA
1.4-2.7	full	0.7	18	1.50	10/50W	1/10W	SMA
1.9-3	full	0.35	20	1.25	10/50W	1/10W	SMA
	500	0.3	23	1.20	10/50W	1/10W	SMA
2-3.5	full	0.4	20	1.30	10/50W	1/10W	SMA
	500	0.4	20	1.30	10/50W	1/10W	SMA
2.5-3.6	full	0.5	20	1.30	10/50W	1/10W	SMA
3.4-4.2	full	0.4	20	1.25	10W	2W	SMA
5-6	full	0.25	23	1.20	10W	2W	SMA
9-10	full	0.3	23	1.20	10W	2W	SMA
8-12	full	0.6	16	1.35	10	20	SMA
12-18	full	0.6	16	1.35	10	20	SMA
8-18	500	0.25	23	1.15	10	20	SMA
	1000	0.3	21	1.20	10	20	SMA