



波导环形器 (waveguide circulator)



型号 (PN)	工作频率 (freq) (GHz)	带宽 (BW) (MHz)	插损 (IL) (dB)	隔离 (IOS) (dB)	驻波 (VSWR)	平均 功率 (average power) (W)	峰值功 率 (peak power) (W)	波导 型号 (interfac e)	外形尺寸 (dimension) L×W×H (mm)
HB32-092	2.7~3.5	300	0.4	20	1.25	200	10000	BJ32	140×140×94
HB48-093	4.2~5.3	400	0.3	20	1.20	600	6000	BJ48	100×100× 63.5
HB58-089	5.0~6.5	300	0.4	20	1.25	1000	8000	BJ58	100×100×80
HB84-088	7.0~9.5	2000	0.4	20	1.25	100	2000	BJ84	60×60×47.8
HB100-118	8.2~12.4	FULL	0.35	20	1.25	200	3000	BJ100	60×52×42
HB120-090	10.0~15.0	FULL	0.4	20	1.25	100	3000	BJ120	50×40×38
HB140-068	11.9~18.0	FULL	0.4	20	1.25	100	3000	BJ140	38×42×33
HB220-066	18~26.5	FULL	0.4	20	1.25	50	500	BJ220	30×30×22.4
HB260-032	22~33	FULL	0.5	17	1.35	30	300	BJ260	57×25×21.1
HB320-098	26.5~40	3000	0.4	20	1.25	20	100	BJ320	45×22×19.1