



波导隔离器 (waveguide isolator)



型号 (PN)	工作频率 (freq) (GHz)	带宽(BW) (MHz)	插损 (IL) (dB)	隔离 (IOS) (dB)	驻波 (VSWR)	平均 功率 (average power) (W)	峰值功 率 (peak power) (W)	波导型号 (interface)	外形尺寸 (dimension) L×W×H (mm)
BG32-099	2.7~3.5	300	0.4	20	1.25	200	10000	BJ32	300×140×140
BG48-101	4.2~5.3	400	0.4	20	1.20	1000	10000	BJ48	160×75×63.5
BG58-085	5.0~6.5	300	0.4	20	1.25	600	6000	BJ58	260×100×80
BG84-066	7.0~9.5	1000	0.4	20	1.25	1000	8000	BJ84	120×60×47.8
BG100-098	8.2~12.4	FULL	0.35	20	1.25	100	1000	BJ100	137×52×41.4
BG120-096	10.0~15.0	FULL	0.4	19	1.25	100	1000	BJ120	110×40×38
BG140-088	11.9~18.0	FULL	0.4	19	1.25	80	1000	BJ140	90×38×33
BG220-118	18~26.5	FULL	0.4	19	1.25	50	500	BJ220	70×30×22.4
BG260-038	22~33	FULL	0.5	17	1.35	30	300	BJ260	57×25×21.1
BG320-089	26.5~40	3000	0.4	20	1.25	20	100	BJ320	45×22×19.1